基于Impala打造交互查询系统

网易杭州研究院

蒋鸿翔

CONTENTS

- 01 交互查询特点
- 02 选型因素
- 03 Impala 基本介绍
- 04 Impala 改进
- 05 Impala 使用场景
- 06 场景方案解析

PART 01

交互查询特点

交互查询特点

数据量基数庞大

关系模型相对较复杂

响应时间要求较高

数据基数庞大

根据数据量选用不同的存储

> 百亿级别，离线数仓，Hive，Spark

百万 ~ 百亿级别，分析型数仓，Impala，Presto，
GreenPlum，Apache Drill

< 百万级别，普通数据库，MySQL，
PostgreSQL

关系模型复杂

宽表型应用

ElasticSearch , Solr , ClickHouse , Druid

组合模型(星型 or 雪花型)

GreenPlum , Presto、 Impala

响应时间要求高

应用场景

在线系统查询
(推荐系统、营销系统等)

BI报表

PART 02

选型因素

选型3大因素

本身项目熟悉度

大厂背书

性能和优缺点指标

选型因素

数据量

性能要求

架构复杂度

运维成本开
销

选型因素

Impala vs Presto vs GreenPlum

- 与Hadoop/Hive兼容
- 成熟的社区环境
- 成熟的架构设计
- 查询性能
- 其他特性

PART 03

Impala 基本介绍

Impala 基本介绍

- A MPP架构
- B 执行节点无状态，去中心化
- C 兼容Hive存储
- D Apache顶级项目，成熟社区
- E 多种数据格式兼容
- F 高效的查询性能

Impala 基本介绍

Impala 基本介绍

Catalogd

- 缓存表元数据
- 缓存HDFS数据块元数据
- DDL操作需要绑定catalogd

Statestored(sub/pub服务)

- Impalad节点状态信息
- 节点资源统计信息
- 元数据信息

Impalad

- SQL解析
- 执行计划生成
- 数据查询、聚合、结果返回
- 非DDL操作不需要catalogd参与

Topic Id	Number of entries	Version	Oldest subscriber version
impalad-query	4	21412	21412
impala-membership	35	189	189
impalad-statistics	35	450258	450258
catalog-update	45778	1147104	1147104
impala-request-queue	70	2131984	2131984

Statestored's topics

Impala 基本介绍

Figure 1: Impala is a distributed query processing system for the Hadoop ecosystem. This figure also shows the flow during query processing.

Impala 基本介绍

高性能因素

元数据缓存

MPP并行计算

Codegen
技术, 支持
LLVM, JIT

支持HDFS
本地读
(shortcircuit)

算子下推
(>, <, In List,
runtime filter)

Impala 基本介绍

并行计算

并行连接 (parallel join)

广播连接
broadcast join

被连接表被传输到所有节点进行连接

适用连接表较小

分区连接
partition join

hash partitioned

适用大表

列统计 (compute stats , 只对hdfs有效)

数据传输代价

CBO

Impala 基本介绍

并行计算

并行聚合
Parallel
Aggregation

数据生成时提前聚合

根据group by的column 进行聚合值的合并操作

数据生成后进行最初的TopN操作
在单节点计划上进行最后的TopN操作

并行
TopN

Impala 基本介绍

存储支持

HDFS

Amazon S3

Azure Data Lake

EMC Isilon storage

HBase

Kudu

Alluxio

MySQL

Impala 基本介绍

授权 & 认证

认证

- Kerberos
- LDAP
- Audit log

授权

- Apache Sentry
 - 粒度：database , table , column
 - 权限：select , insert , all
 - 配置开启
(`authorization_policy_provider_class=org.apache.sentry.provider.file.LocalGroupResourceAuthorizationProvider`)

Impala 基本介绍

资源管理

Admission Control

- fair-scheduler.xml (fair_scheduler_allocation_path)
- llama-site.xml (llama_site_path)

Impala节点通过statestored的impalad-statistics topic项同步资源信息，由于statestored通过心跳与impalad保持通信，这个资源信息实际上有些延迟；目前配置中，只有内存项有实际效果，vcore没有实现隔离，队列名配置如果与认证用户名相同，该用户提交的SQL自动分配到该队列

Impala 基本介绍

Web端

端口

Impalad: 25000

catalogd : 25020

statestored : 25010

基本信息

集群节点

Catalog信息

内存信息

Query信息

.....

Impala 基本介绍

Web端能做什么

节点内存消耗查看

- 每个队列的内存消耗
- 每个查询在该节点内存消耗

```

Process: Limit=100.00 GB Total=8.62 GB Peak=92.55 GB
Buffer Pool: Free Buffers: Total=469.12 MB
Buffer Pool: Clean Pages: Total=0
Buffer Pool: Unused Reservation: Total=-1.75 GB
Free Disk IO Buffers: Total=1.12 GB Peak=1.82 GB
RequestPool=fe-eval-exprs: Total=0 Peak=4.00 KB
RequestPool=default-pool: Total=5.39 GB Peak=85.12 GB
  Query(49415963c2eb0570:f2cfb3ae00000000): Reservation=0 ReservationLimit=80.00
  Query(a245945a93eb0308:c1498d6600000000): Reservation=0 ReservationLimit=80.00
  Query(f4406bdf7ae890f7:66fc610200000000): Reservation=0 ReservationLimit=80.00
  Query(3549750e9111ace4:33b49b9b00000000): Reservation=0 ReservationLimit=80.00
  Query(2f446bbd4706726a:8d6347e900000000): Reservation=0 ReservationLimit=80.00
    
```

该节点上查询分析

- 查询分析
- SQL诊断
- 异常查询终止

1 queries in flight

User	Default Db	Statement	Query Type	Start Time	Duration
hadoop	tpch_parquet_1000_parquet	-- start q10.sql select c_custkey,c_name, sum(l_extendedprice * (1 - l_discount)) as revenue, c_acctbal,n_name,c_address,c_phone,c_comment from customer,orders,lineitem,nation where c_custkey = o_custkey and l_orderkey = o_orderkey and o_orderdate >= '1993-10-01' and o_orderdate < '1994-01-01' and l_returnflag = 'R' and c_nationkey = n_nationkey group by c_custkey,c_name,c_acctbal,c_phone,n_name,c_address,c_comment order by revenue desc limit 100	QUERY	2018-06-23 15:13:58.115437000	2s873ms

Metrics信息查看

.....

Impala 基本介绍

Status: OK

Plan

Query

Text plan

Summary

Profile

Memory

Backends

Plan

Shade nodes according to time spent (if unchecked, shade according to plan fragment)

Impala 基本介绍

Impala缺陷

- Catalogd & statestored服务单点
- Web信息不持久化
- 资源隔离不精确
- 底层存储不能区分用户
- 负载均衡需要外部支持，如Haproxy
- 与Hive元数据同步都需要手动操作

PART 04

Impala 改进

- 基于ZK的loadbalance
- 管理服务器
- 细粒度权限 & 代理
- Json格式
- 兼容ranger权限管理
- 批量元数据刷新
- 元数据同步
- 元数据过滤
- 对接ElasticSearch查询

IMPROVE

PART 05

Impala 使用场景

Impala 使用场景

The screenshot displays the Mammut web interface. At the top, there are navigation tabs for '自助分析' (Self-analysis), '数据管理' (Data management), and '实时流计算' (Real-time stream computing). The main header includes the Mammut logo, '项目中心' (Project center), and the current project 'Impala-滨江二'. The user '蒋鸿翔' is logged in.

The interface is divided into several sections:

- Left Panel:** Contains a 'Query' and 'Notebook' view. A '+ 新建' (New) button is visible. A search bar prompts '请输入文件夹或Query名称'. Below it, a '最近运行的查询' (Recently run queries) section shows a query named 'mammut' selected, and a 'test' folder.
- Center Panel:** Shows a query editor with the text '</> mammut'. The 'limit' is set to 100. The database is set to 'Impala'. There are icons for '保存临时表' (Save temporary table), copy, search, and refresh.
- Right Panel:** Titled '数据信息' (Data information), it shows 'streamdb_impala' and a search bar for '数据表名称' (Data table name). Below this, it indicates '无数据表' (No data table).
- Bottom Panel:** Contains tabs for '运行结果' (Run results), '运行日志' (Run logs), and '执行历史' (Execution history). The '运行结果' tab is active, showing a red error icon and the text '运行失败 (0.1s)' (Run failed (0.1s)). Below this, it says '无结果' (No results).

Impala 使用场景

Impala 使用场景

PART 06

场景方案解析

场景方案解析

需要考虑的问题：

1. 元数据同步问题，ETL写入数据Impala无感知，依赖元数据同步
2. 数据实时性问题，避免大量小文件导致NN不稳定，每次写文件的batch不能太小

场景方案解析

利用Kudu解决小文件问题

关注“UCloud技术公告牌”，更多分享与交流